



# DATAC N 1952

## Waterbased Adhesive

<b>USE</b>	<b>DATAC N 1952</b> has been developed for centre line anchorage of cigarette filter rods. <b>DATAC N 1952</b> has been formulated to meet the German Tabacco Regulations.
<b>PROPERTIES</b>	<b>DATAC N 1952</b> has good hold out, a fast setting speed, is clean machining and has good shear stability.
<b>REMARKS</b>	<b>It is important to ensure that the desired level of adhesion is obtained on the necessary substrates, including long-term tests.</b>

## TYPICAL VALUES

<b>Colour</b>	white
<b>Film</b>	elastic
<b>Viscosity</b>	<u>Brookfield</u> approx. 3.750 mPas (20°C)
<b>pH- Value</b>	approx. 4,5
<b>Solid content</b>	approx. 13 %
<b>Density</b>	approx. 1,01 g/cm <sup>3</sup> (20 °C)
<b>Open time</b>	medium
<b>Setting time</b>	short
<b>Approvals</b>	at request
<b>SHELF LIFE</b>	In original sealed packaging at temperatures between 15 °C and 25 °C up to 3 months.
<b>APPLICATION TYPE</b>	nozzle
<b>CLEANING</b>	Adhesive residues may be washed off with water.
<b>HEALTH &amp; SAFETY</b>	see safety data sheet or label

The information and recommendation contained herein represent the best information available to BTS at the time of preparation.  
This information can be change at anytime without notice.

**BTS srl**

Via Monaldo Calari, 11 – 40011 Anzola Emilia – Bologna – Italy  
Tel 051/6508049 – Fax 051/735154 – e-mail:info@businesstob.com